

### **Countertop** Control Plus Solid Door Refrigerator 47L

GDPA code PPSR47UK

444410570







SKU code

#### Key features

- ✓ 2°C to 8°C temperature range
- Air and core temperature display
- ✓ Represents your vaccine vial
- External digital controller and temperature display
- ✓ Fitted lock and 2 keys
- Audible and visual temperature alarms











#### New controller

New updated Controller system for improved user experience. Read, Record, Reset simply with the touch of one button, with no stress of accidentally resetting on the clear digital display.

### Dual probe

Greater temperature accuracy given from two temperature probe readings. One probe measuring air temperature and one measuring load (or product) temperature.

#### Porthole

Factory fitted 16mm porthole enables quick and easy access for any secondary temperature monitoring probes.

# Flexible internal storage

Multiple shelf locations along with a wire basket provides a flexible storage solution.

# Anti-microbial handle

Powder coated to help prevent cross contamination by inhibiting the growth of microbes.



## **Specification**: Countertop Control Plus Solid Door Refrigerator 47L

Cross Compoity (litros)	47
Gross Capacity (litres) Net Capacity (litres)	30
Unit External Width (mm)	480
Unit External Depth (mm)	505
Unit External Height (mm)	565
Product Weight (kg)	17.5
Packed Width (mm)	490
Packed Depth (mm)	530
Packed Height (mm)	620
Packed Weight (kg)	21
Country of Origin	UK
Internal Dimensions (mm) (WxDxH)	400 x 230 x 415
Temperature Range	+2°C to +8°C (set point tolerance + or -2)
Colour	White/Green
External Finish	Painted Steel
Internal Finish	HIPS*
Type of plastic	SRL800 (HIPS/ABS mix)
Door Finish	Painted Steel/Solid
Door Type	Solid
Door Style	Hinged, Reversible
Door Liner	Flat
Door Open Depth (mm)	905
Replacement Door Seal	No
Open Door Sensor	Yes
Lock	Yes, 2 Keys
Adjustable Feet (number & position)	4 - All adjustable
Porthole	Yes
Porthole Size	16 mm
Porthole Location	Rear LH Corner
Temperature Display on Panel	Yes
Temperature Alarm	Yes
Remote Alarm Contacts	Yes
Audible Alarms	Yes
Visual Alarms	Yes
Number of Shelves	1
Number of Shelf Positions	3
Shelf Size (mm) (WxDxH)	416 X 200
Shelf Material	Wire
Number of Baskets	1
Basket Material	Wire
Basket Size (mm) (WxDxH)	398 x 165
Interior Light	Yes
Light Type	LED
Light Activation	Door Switch/Controller
Fan Spark Free	Yes - Axial No
Defrost Setting	Auto (Off Cycle)
Controller Type	Digital, External
Number of Probes	2
Probe Type	Air & Load (Clycol Solution)
Ambient Temperature Range	10 to 32
Refrigerant Type	R600a
CFC Free	Yes
HFC Free	Yes
HCFC Free	Yes
Ammonia Free	Yes
UK 3 Pin Plug	Yes
Other Plug Types Available	Yes
Voltage Supply	230v
Insulation Thickness (mm)	40
Insulation Type	High Density Polyurothane Foam
Blowing Agent	Cyclopentane
Anti Microbial Handle	Yes
	Yes
Wall Brackets	
Wall Brackets Optional Drawer System	No
	No No

